

## Temperature Probe With Door Status

Part Number: ZW00371SS



### Features:

- 2 in 1 Sensor Module
- Simple and quick to install with sticky pads or screws
- Long battery life and battery level feedback
- Logging & Alarming for each sensor value

- The HALO multifunction sensor provides temperature and door status from single sensor
- The sensor is designed for applications in home automation and light commercial environments
- The technology uses a low-power RF radio system
- Application can include domestic, school, office and light commercial etc monitoring
- Suitable for fridge / freezer monitor, food counter, server racks, plant monitoring

Rated	DC3V (CR123A)
RF Distance	Min. 40M indoor, 100M outdoor line of sight (subject to change due to environmental conditions such as walls, noise, materials etc.)
RF Frequency	868.4MH, 869.85MHz (EU)
RF Maximum Power	+10dBm (Peak), -10dBm (Average)
Battery Life	CR123A 2~5 years (Depending on the trigger interval)
Dimension	85(L) x 28(W) x 23(H) mm
Weight	80g
IP Classification	IP20; indoor use
Operation Temperature	-10 to 40° C (+/- 1.5 °C)
Humidity	85% RH max
Magnetic Gap	25mm (open to close); 30mm (close to open)
Temperature Detect Range	-30 to 100° C
Cable Type	28AWG x 4C OD: 3.0mm, 2 meters, -40 to 80° C